

REPLACED BY
ART 34 AMDT

CLAIMS

1. A mechanism including:

a piston-and-cylinder assembly including a piston

5 housed in a cylinder,

a pin member passing through the piston and

a guide member having a guide recess accommodating an
end of the pin member,

10 the guide recess being so shaped and orientated in
relation to the piston-and-cylinder assembly that a common
axis exists between the guide recess and the piston-and-
cylinder assembly,

the guide member and the piston-and-cylinder assembly
being so mounted as to be rotatable relative to each other
15 about the common axis and

the guide recess being a figure-8 in shape bounded by
an outer and an inner periphery, for guiding the pin member
continuously in a figure-8 path, causing the piston to
sweep up and down the cylinder, when the guide member and
20 the piston-and-cylinder assembly rotate relative to each
other,

the radius of curvature of the section of the outer
periphery of the guide recess determining piston movement
during the induction stroke being smaller than the radius
25 of curvature of the sections of the inner periphery of the
guide recess determining piston movement during the
compression, expansion and exhaust strokes, of the
operating cycle.

30 2. A mechanism including:

a piston-and-cylinder assembly including a first
piston housed in a first cylinder and a second piston
housed in a second cylinder,

a first pin member passing through the first piston and a second pin member passing through the second piston and

5 a guide member having a guide recess accommodating an end of the first pin member and an end of the second pin member,

10 the guide recess being so shaped and orientated in relation to the piston-and-cylinder assembly that a common axis exists between the guide recess and the piston-and-cylinder assembly,

the guide member and the piston-and-cylinder assembly being so mounted as to be rotatable relative to each other about the common axis and

15 the guide recess being a figure-8 in shape bounded by an outer and an inner periphery, for guiding the pin members continuously in a figure-8 path, causing the piston to sweep up and down the cylinder, when the guide member and the piston-and-cylinder assembly rotate relative to each other,

20 the radius of curvature of the section of the outer periphery of the guide recess determining piston movement during the induction stroke being smaller than the radius of curvature of the sections of the inner periphery of the guide recess determining piston movement during the
25 compression, expansion and exhaust strokes, of the operating cycle.

3. A mechanism as claimed in claim 2, wherein the form of the piston-and-cylinder assembly permits the first and
30 second cylinders to lie diametrically opposed to each other.

4. A mechanism as claimed in claim 2, including a further cylinder, a further piston in the further cylinder and a further pin member passing through the further piston and being accommodated in the guide recess, the first, second
5 and further cylinders being spaced 120° apart.

5. A mechanism as claimed in claim 3, including at least one further pair of diametrically opposed cylinders on the piston-and-cylinder assembly,
10 further pistons in the further cylinders and further pin members passing through the pistons and being accommodated in the guide recess.

6. A mechanism as claimed in claim any one of claims 1 to
15 5, wherein the ratio of the radius of curvature of the section of the outer periphery of the guide recess determining piston movement during the induction stroke to the radius of the radius of curvature of the sections of the inner periphery of the guide recess determining piston
20 movement during the compression, expansion and exhaust strokes lies in the range from about 0.95 to about 0.01, both limits included.

7. A mechanism as claimed in any one of claims 1 to 6,
25 wherein the ratio of the radius of curvature of the section of the outer periphery of the guide recess determining piston movement during the induction stroke to the radius of the radius of curvature of the sections of the inner periphery of the guide recess determining piston movement
30 during the compression, expansion and exhaust strokes lies in the range from about 0.85 to about 0.15, both limits included.

8. A mechanism as claimed in any one of claims 1 to 7,
wherein the ratio of the radius of curvature of the section
of the outer periphery of the guide recess determining
piston movement during the induction stroke to the radius
5 of the radius of curvature of the sections of the inner
periphery of the guide recess determining piston movement
during the compression, expansion and exhaust strokes lies
in the range from about 0.75 to about 0.25, both limits
included.

10

9. A mechanism as claimed in any one of claims 1 to 8,
wherein the ratio of the radius of curvature of the section
of the outer periphery of the guide recess determining
piston movement during the induction stroke to the radius
15 of the radius of curvature of the sections of the inner
periphery of the guide recess determining piston movement
during the compression, expansion and exhaust strokes lies
in the range from about 0.65 to about 0.35, both limits
included.

20

10. A mechanism as claimed in any one of claims 1 to 9,
wherein the ratio of the radius of curvature of the section
of the outer periphery of the guide recess determining
piston movement during the induction stroke to the radius
25 of the radius of curvature of the sections of the inner
periphery of the guide recess determining piston movement
during the compression, expansion and exhaust strokes lies
in the range from about 0.55 to about 0.45, both limits
included.

30

11. A mechanism as claimed in any one of claims 1 to 10,
wherein the radius of curvature of the section of the outer
periphery of the guide recess determining piston movement

during the induction stroke is of the order of a half of the radius of curvature of the sections of the inner periphery of the guide recess determining piston movement during the compression, expansion and exhaust strokes.

5

12. A mechanism as claimed in any one of claims 1 to 8, wherein the radius of curvature of the section of the outer periphery of the guide recess determining piston movement during the induction stroke is of the order of two-thirds
10 of the radius of curvature of the sections of the inner periphery of the guide recess determining piston movement during the compression, expansion and exhaust strokes.

13. A mechanism as claimed in any one of claims 1 to 8,
15 wherein the radius of curvature of the section of the outer periphery of the guide recess determining piston movement during the induction stroke is of the order of between two-thirds and a half of the radius of curvature of the sections of the inner periphery of the guide recess
20 determining piston movement during the compression, expansion and exhaust strokes.

14. A mechanism as claimed in any one of claims 1 to 13, including a second guide member having a second guide
25 recess accommodating the other end of the pin member or the other ends of the pin members, the second guide recess being so shaped and orientated in relation to the piston-and-cylinder assembly as to share the common axis existing
30 between the first guide recess and the piston-and-cylinder assembly, the second guide recess being of the same form as the first guide recess.

15. A mechanism as claimed in any one of claims 1 to 14, including axial slots in the cylinder or the cylinders, the pin member or pin members engaging the axial slots, to serve as guide means to the piston or pistons.

5

16. A mechanism as claimed in claim 15, wherein the axial slots lie on a diameter of the cylinder or cylinders.

17. A mechanism as claimed in any one of claims 1 to 16,
10 including guide means for the piston or pistons so positioned as to engage the piston shank or piston shanks.

18. A mechanism as claimed in claim 17, wherein the or each piston shank includes a rectangular portion and the
15 guide means is of complementary shape and engages the rectangular portion of the or each piston shank.

19. A mechanism as claimed in claim 18, wherein the or each piston shank includes an H-form transverse cross-
20 section portion.

20. A mechanism as claimed in claim 18 or claim 19, wherein the or each piston shank includes an H-form transverse cross-section portion and the horizontal element
25 of the H projects beyond both of the vertical elements of the H.

21. A mechanism as claimed in any one of claims 1 to 20, wherein common axis is the axis of a shaft on which the
30 piston-and-cylinder assembly is rotatably mounted, the remainder of the mechanism being fixed.

22. A mechanism as claimed in any one of claims 1 to 20,
wherein the common axis is the axis of a shaft on which the
guide member is rotatably mounted or the guide members are
rotatably mounted, the piston-and-cylinder assembly being
5 fixed.

23. A mechanism as claimed in any one of claims 1 to 20,
wherein the common axis is the axis of a shaft on which the
guide member is or the guide members are rotatably mounted,
10 and the piston-and-cylinder assembly is rotatably mounted
on the shaft.

24. A mechanism as claimed in any one of claims 1 to 23,
including bearing means at the end of the pin member or the
15 ends of pin members accommodated in the guide recess, for
effecting rolling contact between the peripheries of the
guide recess and the end of the pin member or the ends of
the pin members.

20 25. A mechanism as claimed in claim 24, wherein the
bearing means at the end of the pin member or the ends of
the pin members includes an outer bearing assembly
contacting only the outer periphery of a guide recess and
an inner bearing assembly contacting only the inner
25 periphery of the guide recess.

26. A mechanism as claimed in claim 25, wherein the outer
bearing assembly includes an outer cylindrical shell
supported by a plurality of outer rollers on the pin
30 member, the outer cylindrical shell lying in contact with
the outer periphery only of the guide recess.

27. A mechanism as claimed in claim 26 or claim 26,
wherein the inner bearing assembly includes an inner
cylindrical shell supported by a plurality of inner rollers
on the pin member, the inner cylindrical shell lying in
5 contact with the inner periphery only of the guide recess.

28. A mechanism as claimed in claim 26 or claim 27,
wherein the outer and inner bearing assemblies are so
mounted that the outer and inner cylindrical shells rotate
10 about the same axis.

29. A mechanism as claimed in any one of claims 26 to 28,
wherein the outer and inner bearing assemblies are so
mounted that the outer and inner cylindrical shells rotate
15 about the axis of the pin member.

30. A mechanism as claimed in claim 26 or claim 27,
wherein the outer and inner bearing assemblies are so
mounted that the outer cylindrical shell rotates about an
20 axis which is offset from the axis about which the inner
cylindrical shell rotates.

31. A mechanism as claimed in any one of claims 26 to 29,
wherein the bearing means includes a ball bearing between
25 the outer and inner bearing assemblies, the balls of the
ball bearing running in tracks in the outer and inner
cylindrical shells.

32. A mechanism as claimed in any one of claims 1 to 31,
30 including a guide recess having an inner periphery
including a step in its profile for accommodating bearing
means at the end of the pin member or the ends of the pin
members, the bearing means including an outer bearing

assembly contacting only the outer periphery of a guide recess and an inner bearing assembly contacting only the inner periphery of the guide recess.

5 33. A mechanism as claimed in any one of claims 1 to 32, including a guide recess having an outer periphery the surface of which is narrower than the surface of the inner periphery, bearing means at the end of the pin member or the ends of the pin members including an outer bearing
10 assembly contacting only the narrower surface of the outer periphery of a guide recess and an inner bearing assembly contacting only the surface of the inner periphery of the guide recess.

15 34. A mechanism as claimed in any one of claims 1 to 33, wherein a plurality of apertures are included in the pin member or pin members for receiving and distributing lubricant to the end of the pin member or pin members.

20 35. A mechanism as claimed in claim 34, including a guide member having at least one aperture so positioned as to permit the delivery of lubricant through the guide member to the pin member or pin members.

25 36. A mechanism including:
a piston-and-cylinder assembly including a piston housed in a cylinder,
a pin member passing through the piston and
a guide member having a guide recess accommodating an
30 end of the pin member,
the guide recess being so shaped and orientated in relation to the piston-and-cylinder assembly that a common

axis exists between the guide recess and the piston-and-cylinder assembly,

the guide member and the piston-and-cylinder assembly being so mounted as to be rotatable relative to each other
5 about the common axis and

the guide recess being a figure-8 in shape bounded by an outer and an inner periphery, for guiding the pin member continuously in a figure-8 path, causing the piston to sweep up and down the cylinder, when the guide member and
10 the piston-and-cylinder assembly rotate relative to each other,

the guide recess having an inner periphery including a step in its profile accommodating bearing means at the end of the pin member or the ends of the pin members, the
15 bearing means including an outer bearing assembly contacting only the outer periphery of a guide recess and an inner bearing assembly contacting only the inner periphery of the guide recess.

20 37. A mechanism as claimed in claim 36, including a guide recess having an outer periphery the surface of which is narrower than the surface of the inner periphery, bearing means at the end of the pin member or the ends of the pin members including an outer bearing assembly contacting only
25 the narrower surface of the outer periphery of a guide recess and an inner bearing assembly contacting only the surface of the inner periphery of the guide recess.

30 38. A guide member, for a piston-and cylinder assembly, having a guide recess accommodating an end of a pin member passing through a piston of the piston-and-cylinder assembly,

the guide recess being a figure-8 in shape bounded by an outer and an inner periphery, for guiding the pin member continuously in a figure-8 path,

5 the radius of curvature of the section of the outer periphery of the guide recess determining piston movement during the induction stroke being smaller than the radius of curvature of the sections of the inner periphery of the guide recess determining piston movement during the compression, expansion and exhaust strokes, of the
10 operating cycle.

39. A guide member as claimed in claim 38, wherein the radius of curvature of the section of the outer periphery of the guide recess determining piston movement during the
15 induction stroke is of the order of a half of the radius of curvature of the sections of the inner periphery of the guide recess determining piston movement during the compression, expansion and exhaust strokes.

20 40. A guide member as claimed in claim 39, wherein the radius of curvature of the section of the outer periphery of the guide recess determining piston movement during the induction stroke is of the order of two-thirds of the radius of curvature of the sections of the inner periphery
25 of the guide recess determining piston movement during the compression, expansion and exhaust strokes.

41. A guide member as claimed in claim 39, wherein the radius of curvature of the section of the outer periphery
30 of the guide recess determining piston movement during the induction stroke is of the order of between two-thirds and a half of the radius of curvature of the sections of the inner periphery of the guide recess determining piston

movement during the compression, expansion and exhaust strokes.

5 42. A heat engine including a mechanism as claimed in any one of claims 1 to 41, wherein the pistons and cylinders are pistons and cylinders of the heat engine and, in operation, generate motive power for the mechanism.

10 43. A heat engine as claimed in claim 42, which is an internal combustion engine.

44. An engine as claimed in claim 42 or claim 43, which is a Diesel-cycle engine.

15 45. An engine as claimed in claim 42 or claim 43, which is an Otto-cycle engine.

46. An engine as claimed in claimed in any one of claims 42 to 45, which is a four-stroke engine.

20

47. An engine as claimed in any one of claims 42 to 45, which is a two-stroke engine.